

Appl. No. 10/085,393
 Amdt. Dated Aug. 8, 2003
 Reply to Office Action of Ma 2003

Amendments to the Claims

Claim 1 (currently amended): A variable optical attenuator for attenuating optical signals transmitted from an input fiber to an output fiber, comprising:

a rotatable mechanism between the input fiber and the output fiber; and

a refractor mounted on and being rotatable with the rotatable mechanism which is given to deflect light beams from the input optical fiber and then to couple part of the light beams into the output fiber, the refractor being rotatable to different angles to change the incident angle of the input light beams and then to output refracted light beams that are deflected from the axis of the input light beams as determined by the incident angle to continuously change the amount of the light beams entering into the output fiber.

Claim 2 (currently amended): The variable optical attenuator as claimed in claim 1, further comprising two collimators—ferrules for containing the input fiber and the output fiber, respectively.

Claim 3 (original): The variable optical attenuator as claimed in claim 1, wherein the rotatable mechanism comprises a fixing block and a rotatable post extending from the bottom of the fixing block.

Claim 4 (currently amended): The variable optical attenuator as claimed in claim 1, further comprising a holder to rotatably hold the rotatable mechanism and hold the two collimators in alignment with each other.

Claim 5 (original): The variable optical attenuator as claimed in claim 1, wherein the refractor is a lens.

Claim 6 (original): The variable optical attenuator as claimed in claim 5, wherein the refractor has two parallel surfaces.

Appl. No. 10/085,393
 Amdt. Dated Aug. 8, 2003
 Reply to Office Action of May 9, 2003

Claim 7 (original): The variable optical attenuator as claimed in claim 6, wherein the refractor has anti-reflective coatings covering the two parallel surfaces.

Claim 8 (original): A variable optical attenuator comprising:

an input port and an output port facing to each other along an axial direction, said input port including an input GRIN lens and an input ferrule, said output port including an output GRIN lens and an output ferrule;

a refractor positioned between said input port and said output port, said refractor being rotatable about an axis perpendicular to said axial direction; wherein

when said refractor extends perpendicular to said axial direction, light from the input GRIN lens penetrates said refractor and substantially fully enters the output GRIN lens while when said refractor is tilted relative to the axial direction with therebetween an angle different from ninety degrees, attenuation occurs

Claim 9 (currently amended): The attenuator as claimed in claim 8, wherein said attenuation follows a formula as follows:

Attenuation = $-10 \log \eta$, where η is lateral displacement effect between an

axis of the input beam and an axis of the output beam, given by $\eta = 2 \times$

$\cos^{-1}(d/a)/\pi - d \times \text{SQRT} [1 - (d/2a)^2] / \pi a$ and $d = h \times \sin (\theta - \sin^{-1}(\sin \theta / n))$

$/\cos [\sin^{-1}(\sin \theta / n)]$, wherein

θ is an incident angle for an input beam from the input GRIN lens with regard to the refractor;

Appl. No. 10/085,393
Amdt. Dated Aug. 8, 2003
Reply to Office Action of May 9, 2003

n is an index of refraction;

d is a lateral deflection relative to the axis of the input beam;

a is a core radius of an optic fiber used in the attenuator; and

h is a thickness of the refractor.

Claim 10 (new): A variable optical attenuator comprising:

an input port;

an output port;

a holder coaxially fixing the input and output ports at two sides thereof;

a refractor positioned between the input and output ports; and

a rotatable mechanism mounted in the holder and being rotatable about an axis perpendicular to an optical axis of the input port, said refractor being fixed on the rotatable mechanism.

Claim 11 (new): The variable optical attenuator as claimed in claim 10, wherein the rotatable mechanism has a fixing block and a rotatable post extending from a bottom of the fixing block.

Claim 12 (new): The variable optical attenuator as claimed in claim 11, wherein the fixing block of the rotatable mechanism has a groove defined in a center of a top surface thereof, for fixing the refractor.

Claim 13 (new): The variable optical attenuator as claimed in claim 12, wherein the holder has a base and two side walls respectively perpendicularly extending from two sides of the base, and each side wall has a mounting hole defined therethrough for fixing the input port or the output port.

Claim 14 (new): The variable optical attenuator as claimed in claim 13, wherein a center hole is defined in a center of the base for

Appl. No. 10/085,393
Amdt. Dated Aug. 8, 2003
Reply to Office Action of May 9, 2003

inating with the rotatable post of the rotatable mechanism.

Claim 15 (new): The variable optical attenuator as claimed in claim 14, wherein the refractor has anti-reflective coatings covering two surfaces which respectively face the input and output ports.

BEST AVAILABLE COPY